

The **PoolMatch** display is a professional pump suitable for use in Swimming Pool markets.



FEATURES

- IP65 Level Protection
- Alphanumeric Display
- Wheel holder mounted on ball bearing, for a longer pump life
- New motors with extended life time
- Snap on transparent cover
- Two roller PTFE body, for a more proportional dosing and an extended lifetime
- Serial Port Rs485 with Modbus RTU protocol communication
- Wi-Fi module enables pool management via SekoLink APP, it is an intuitive smartphone app that grants users quick and easy access to key water-quality parameters for their pool or SPA

TECHNICAL CHARACTERISTICS

- **FLOW RATES**
 - 1,6 l/h;
- **BACK PRESSURE**
 - 1,5 bar
- **POWER SUPPLY**
 - 230±Vac - 50/60 Hz - 10W with galvanized insulation
- **MATERIALS**
 - **ENCLOSURE:** ABS with fiber glass
 - **PUMP HEAD:** PP
 - **TUBES:** Santoprene
- **DOSING**
 - proportional mode
- **MOTORS**
 - Brushed AC Motors
- **MEASURE**
 - 3 ÷10 pH measure
 - 200 ÷999 Redox measure
- **FUNCTIONS**
 - Proportional dosing by pH feedback measure

PUMP KEY CODE

1	Pool Series							
	2-3	Measure version: pH, mV(ORP),						
		4-5	Version PoolMatch					
			6	Standard				
				7	Peristaltic pump			
					8	Power Supply: A= 220 Vac		
						9	Peri Tube: 1=Santoprene	
							10	Optional
								11-12 Free
S	PH	PM	S	P	A	1	N	00

Code	Descrizione	Version
SMVPMSPA1N00	POOLMATCH RX 1,6L/H 1,5 BAR 230 VAC	ORP
SMVPMSPA1S00	POOLMATCH RX 1,6L/H 1,5 BAR 230 VAC MODBUS	OPR with ModBus
SMVPMSPA1W00	POOLMATCH RX 1,6L/H 1,5 BAR 230 VAC MODBUS	OPR with WiFi
SPHPMSPA1N00	POOLMATCH PH 1,6L/H 1,5 BAR 230 VAC	pH
SPHPMSPA1S00	POOL MATCH PH 1,6L/H 1,5 BAR 230 VAC MODBUS	pH with Modbus
SPHPMSPA1W00	POOL MATCH PH 1,6L/H 1,5 BAR 230 VAC MODBUS	pH with WiFi

DIMENSIONS

