



Code: 9900105007

Features:

- Low maintenance sealed unit
- Gel filled reference cell
- S8 connection with PG 13,5 mm
- Glass Body for High Pressure Environmental
- Three ceramic diaphragm type

Field Application:

- Ammonia application
- Chromium plating
- Reverse Osmosis
- Bisulphite application
- Galvanic Process

Features:

- Range: pH 0÷14
- Temperature: 0÷130 °C (* until to 6 bar)
- Pressure: 16 Bar (*until to 25°C)
- Trasparten glass Body
- **Double junction** with KCL Gel and **three ceramic diaphragm**.
- S8 connector: PG13,5 mm mechanical connection and S7 electrical connection.
- Batch production number.
- Single Package with neutral carton box.
- Neutral Label.

TECHNICAL CHARACTERISTICS

pH Range:	0 ÷ 14
Min. Conductivity:	50 µS/cm
Temp. Range:	130° C
Pressure Range:	6 bar at 130°C 16 bar at 25° C
Body material:	Glass
Diaphragm material:	Glass
Diaphragm Type:	3 ceramic nut
Mechanical Mounting:	PG 13.5
Electrical Connection:	S8
Reference:	GEL
Storage temperature	+2 ÷50 °C (do not freeze)

DIMENSIONS

